



Printer compatibility 385nm (UV)









# MATERIAL PROCESSING GUIDE - DENTAIBT

# **SAMPLE ONLY NOT FOR MEDICAL USE**

### **APPLICATIONS**

Indirect bonding trays

# HANDLING / SAFETY / STORAGE

Wear disposable nitrile gloves at all times when handling liquid resin.

Avoid contact with skin. If contact with skin occurs wash thoroughly with cold soapy water.

If contact with eyes occur seek immediate medical assistance.

Storage on printer for up to 4 weeks with hood closed. Store in bottle for up to 24 months in a cool dark place.

#### INI FII F

Ensure you are using the latest material ini file. You can access the latest material ini file for this material in your Asiga account online here: https://www.asiga.com/accounts/#tab material

### MIXING

In Bottle

Agitate/shake bottle well prior to pouring.

Stir material with a soft spatula. Take care not to damage film of Build Tray

#### PRINTING

Ensure film on the Build Tray is clear of any debris before starting the next print.

# WASHING

In a well ventilated area, wash parts thoroughly in IPA 98%+ pure (Isopropyl alcohol).

Important: ensure a dedicated bath is used for this material. Do not wash in baths that have previously been used for other materials.

Using an ultrasonic cleaning device:

- Pre-wash bath: 5 minutes
- Post-wash bath: 5 minutes

Allow parts to air dry





## **POST CURING**

Place parts in Nk Optik Otoflash G171 under Nitrogen for 2000 flashes each side (Total: 2x 2000 flashes)

For MSDS or technical assistance open a support ticket in your account online. https://www.asiga.com/accounts/support/